FRANKFURT MAIN
RNAV (GPS)
RWY 25L

ATIS	118.025	DIRECTOR	119.025	APRON	121.700
LANGEN RADAR (N)	120.800	TOWER	119.900		121.850
LANGEN RADAR (S)	118.450	GROUND	121.800		121.950

ELEV 364
OCH RELATED TO THR 25L ELEV 362
VAR 1° E

INSTRUMENT APPROACH CHART - ICAO

MISSED APPROACH PROCEDURE
RNAV (GPS)
On track 249° to DF290; LT on track 233° to DF291; RT on track 244° climb 4000; LT to CHA climb and maintain 5000.

DF290[L] - DF291[R] - [A4000+; L] - CHA [A5000]

NON-RNAV
Climb straight ahead to 5.5 DME FFM; LT to intercept R244 FFM; on R244 FFM to 8.0 DME FFM or 4000, whichever is later; LT to CHA VOR climb and maintain 5000.

OCA (OCH)	A	B	C	D
GPS	830 (470)	830 (470)	830 (470)	830 (470)

DIST THR / RW25L	2	3	4	5	6	7	8	9	10	11
ALTITUDE	1050	1370	1690	2010	2330	2650	2960	3280	3600	3920

Timing not authorized for defining the MAPt.

GS	kt	80	100	120	140	160	180
LEDKI - RW25L (11.2 NM)	MIN:SEC	8:24	6:43	5:36	4:48	4:12	3:44
Rate of descent (5.2%)	ft / MIN	420	530	640	740	850	960

Correction: Communications, Note withdrawn.

© DFS Deutsche Flugsicherung GmbH