INSTRUMENT APPROACH CHART - ICAO

VAR 1° E

ELEV 364
OCH RELATED TO THR 07L ELEV 329

ATIS	118.025	DIRECTOR	119.025	APRON	121.700
LANGEN RADAR (N)	120.800	TOWER	119.900		121.850
LANGEN RADAR (S)	118.450	GROUND	121.800		121.950

FRANKFURT MAIN
RNAV (GPS)
RWY 07L

MISSED APPROACH PROCEDURE RNAV (GPS)
Climb on track 070° via FR to DF273 or 5000, whichever is later; LT to TAU maintain 5000.

FR - DF273 - [A5000; L] - TAU [A5000]

NON-RNAV
Climb straight ahead via FR LO to 10.0 DME FRD or 5000, whichever is later; LT to TAU DVORTAC maintain 5000.

OCA (OCH)	A	B	C	D
GPS	830 (500)	830 (500)	830 (500)	830 (500)

DIST THR / RW07L	11	10	9	8	7	6	5	4	3	2
ALTITUDE	3890	3570	3250	2930	2610	2290	1980	1660	1340	1020

Timing not authorized for defining the MAPt.

GS	kt	80	100	120	140	160	180
LOMPO - RW07L (11.3 NM)	MIN:SEC	8:29	6:47	5:39	4:51	4:14	3:46
Rate of descent (5.2%)	ft / MIN	420	530	640	740	850	960

Correction: Communications, FRD DME renamed to FRED, Note.

© DFS Deutsche Flugsicherung GmbH